



**TDS**  
**VENOL GEAR GL-4 85W-90**

**Characteristic:**

Mineral oil for vehicle transmission gears that provides excellent lubricating and anti-rust properties, high oxidization resistance and high load carrying capacity. Thanks to the AW and EP additives, GL-4 85W-90 oil provides very good anti-wear and antifricition properties. The oil is used to lubricate back axles and transmission gears of the vehicles working under severe conditions.

**Specifications:**

Viscosity grade: SAE 85W/90

Quality class: API :GL-4

Meets the requirements:

MAN 342 Type M1, Mercedes Benz 235.0, MIL-L-2105D

Voith 3.325-339, Volvo 97310, DAF

<b>VENOL GL-4 85W/90</b>	<b>Typical values</b>
Viscosity at 100°C, mm <sup>2</sup> /s	<b>14,5</b>
Viscosity index, min	<b>120</b>
TAN, min ( mg KOH/g)	<b>0,2</b>
Pour point, max °C	<b>-27</b>
Flash point, min °C	<b>200</b>

Venol Motor Oil GmbH  
Litauische Str. 43  
15234 Frankfurt Oder  
Ust-Id- Nr DE-319472195  
ST-NR 061/121/03730  
HRB 93818

**Geschäftsführer:** Maciej Filip Gostynski  
Bankverbindung: DE 38 4401 0046 0408 0114 61  
BIC: PBNKDEFF  
Tel. 0049 335 401 44 01  
venol@venol.pl