



BODY 600 ECO PAINT REMOVER

Technical Data Sheet



General Technical Description

Easy to use
Excellent results

Surface

Suitable for the removal of paint, clear coats and latex materials from all metal and plastic surfaces.

Pretreatment / Cleaning of substrate

Product Application:

»» Apply one to two hands till the area needed to be cleaned is all covered with the paint remover. Allow for the product to work for about 15 min. Use a spatula and lightly scrape off the residues of paint remained. In case of strong paint residues re-apply the product on the surface till all the old paint is removed.

Flash Point:
-18°C

Specific Gravity:
0.982 g/cm³

Solid Content (No thinner):
3% Weight

VOC (2004/42/EC)
Not applicable

Theoretical Coverage:
-

Remarks:

- Always try to use the product in accordance with the specifications provided.
- It can be used by countries that do not adopt the VOC legislation.

Storage shelf life:

- Up to 12 months storage time of unopened tins
- (+5 to +25°C)

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

Issue 1/2014, July 2014