


PROMOTOR 895

Plastic Adhesion Promoter



DESCRIPTION

Adhesion promoter for a wide range of plastic parts in the automotive sector, garden furniture or other hard plastic objects. Applicable on the following types of plastic: PP, PUR, PS, PA, PP-EPDM, ABS, PVC, GRP, PC. For other types of plastic, please consult our technical department.

It is suitable for the application on patches and/or small surfaces. It is very easy to apply and allows a high power of adhesion on the indicated substrates.

COLORS

PROMOTOR 895	COLORLESS
--------------	-----------

SURFACE PREPARATION

Remove dirt with soap and water. Once the surface to be painted is dry, degrease it with URKISOL 94 Plastic Degreaser.

If the surface of the plastic is not even, we recommended to heat the part to make any residue come out to the surface to obtain a good cleaning of it.





If necessary, it can be sanded with fine-grained sandpaper (P600) and then degreased to remove dust before applying the promoter.

It can be repainted with most common finishing paints and enamels.

USE

Recommended with gravity spray gun. Apply 1 thin coat on the desired surface. No thinner dilution required.

APPLICATION

 <p>Gravity Gun Application pressure</p>	<p>1.3-1.5 mm 2-2.5 bar</p>
 <p>Number of coats Total thickness</p>	<p>1 coat 2-4 µm</p>
 <p>Flash time</p>	<p>2'</p>
 <p>Drying Time 20°C</p>	<p>5'</p>

SAFETY INSTRUCTIONS 

The use of appropriate personal protective equipment is recommended during application, to prevent the irritation of the respiratory tract, skin and eyes. For professional use only.

STORAGE 

Keep in a tightly covered container, in a dry and ventilated place, avoiding direct exposure to sunlight. Temperature above 5°C is recommended, between 15 and 30°C optimal.

VOC 

The VOC content of **PROMOTOR 895** is a maximum of 840 g/l in compliance with European regulation 2004/42/EC IIB(E) (840) <840 g/l.

The information contained in this Technical Specification Sheet is based on the knowledge and experience of the BESA technical department, and with it it's intended to advice and inform, being the responsibility of the user to take the necessary measures to guarantee the intended purpose of the product. **FOR PROFESSIONAL USE ONLY.**
